

2. LIFTING FRAME

Features:

Load Security: Lashing rings inside to secure cargo

Area: Stackable to minimize deck area usage on location

Open roof and removable hatch options



Specifications:

Equipment	External Dimensions (Lx Wx H)	Internal Dimensions (Lx Wx H)	Tare	Payload	M.G.W	Internal Cubic Capacity
10ft Lifting Frame Type 1 Closed Roof	2.99 x 2.43x 2.59 m 10' x 8' x 8'6"	2.77 x 2.17 x 2.24 m 9'x7'1x"	2,300 kgs 5,070 lbs	12,000 kgs 26,455 lbs	14,300 kgs 31,525 lbs	13.4 m ² 473 cu.ft
10ft Lifting Frame Type 2 Open Roof	2.99 x 2.43x 2.59 m 10' x 8' x 8'6" f	2.77 x 2.17 x 2.24m	1,500 kgs 3,306 lbs	5,000 kgs 11,023 lbs	6,500 kgs 14,330 lbs	14.3 m ³ 504 cu.ft
15ft Lifting Frame Type 1 Open Roof	4.57 x 2.43x 2.59 m 15' x8' x 8'6"	4.25 x 2.11 x 2.26 m 13'11" x7'x7"4" f	1,970 kgs 4,343 lbs	6,000 kgs 13,227 lbs	7,970 kgs 17,570 lbs	20.4 m' 720 cuff
20ft Lifting Frame Type 1 Hatch Roof	6.05 x 2.43x2.89 m 20' x 8' x 9'6" f	5.63 x 2.11 x 2.51 m 18'6" x 6'11" x83" l	5,100 kgs 11,243 lbs	19,900 kgs 43,872 lbs	25,000 kgs 55,115 lbs	30 m ² 1059 cu.ft
20ft Lifting Frame Type 2 Open Roof	6.05 x 2.43 x 2.59 m 20' x 8' x 9'6"	5.73 x 2.11 x 2.27 m 18'9" x6'11" x7'5"f	2,600 kgs 5,732 lbs	8,000 kgs 17,636 lbs	10,600 kgs 23,368 lbs	27.5 m ² 971 cu.ft
24 10ft Lifting Frame Over-sized	7.32 x 3.32 x 3.02 m 10'10" x 9'10" ft	7.00 x 3.00 x 2.58 m 22'11" x9'10"x8'5" lt	8,000 kgs 17,640 lbs	40,000 kgs 88,180 lbs	48,000 kgs 105,820 lbs	54.8 m ³ 1935 cu.ft

Key Features:



Equipment	Specification	Key Features
Lifting Frame	DNV 2.7-1, DNV 2.7-3, BS EN 12079 & ISO/CSC	Design, Manufacture & Certification - DNV 2.7-1 offshore containers - DNV 2.7-3 portable offshore units - BS EN 12079:2006 offshore containers: Design, construction, testing, inspection & marking - Classification society: Lloyds Register - Lifting: Third party lifting certification provided for container and sling set and all lifting equipment Other Features - Sizes: 10ft, 15ft, 20ft and 24ft options - Load security: Lashing rings built into floor to secure cargo - Area: Stackable to minimise deck area usage on location - Open roof and removable hatch options - 24ft lifting frame holds 2 x 10ft or 1 x 20ft ISO/CSC container