

3. WORKSHOP CONTAINER

Features:

Insulation: PU sandwich panels, 50mm thick on the sides and 100mm on the roof

Electrics: Switch and Power sockets 110v and 240v round plug/pin options - safe area

Work Area: Workbench complete with vice and under-bench storage shelves

Storage: Removable bolted door to roof storage cupboard with shelving and double doors.

Stackable to minimize deck area usage on location

Lifting: Central runway beam complete with low headroom trolley/ electric hoist

Safety: Anti-slip studded rubber mat floor

Welfare: AC units are built into 2 types of units



Specifications:

Equipment	External Dimensions (Lx Wx H)	Internal Dimensions (Lx Wx H)	Tare	Payload	M.G.W	Internal Cubic Capacity
10ft Workshop Container - Type 1	2.99 m x 2.43 m x 2.59 m 9'9" x 8' x 8'6"ft	2.83 x 2.24 x 2.32 m 9'3" x 7'7" x 7'7"ft	2,200 kgs 4,850 lbs	7,800 kgs 17,195 lbs	10,000 kgs 22,045 lbs	14.7 m ³ 519 cu.ft
10ft Workshop Container - Type 2	2.99 x 2.43 x 2.59 m 9'9" x 8'x 8'6"ft	2.80 x 2.28 x 2.23 m 9'2" x 7'5" x 7'4"ft	2,200 kgs 4,850 lbs	7,800 kgs 17,195 lbs	10,000 kgs 22,045 lbs	14.3 m ³ 504 cu.ft
20ft Workshop Container - Type 1	6.05 x 2.45 x 2.59 m 19'10" x 8' x 8'6"	5.89 x 2.24 x 2.32 m 19'2" x 7'7" x 7'4"ft	3,650 kgs 8,050 lbs	10,000 kgs 22,040 lbs	13,650 kgs 30,100 lbs	30.8 m ³ 1087 cu.ft
20ft Workshop Container - Type 2	6.05 x 2.45 x 2.59 m 19'10" x 8' x 8'6"	5.86 x 2.30 x 2.21 m 19'2" x 7'6" x 7'3"ft	3,700 lbs 8,157 lbs	10,000 kgs 22,040 lbs	13,700 lbs 30,203 lbs	30. m ³ 1059 cu. ft

Key Features:



Equipment	Specification	Key Features
Workshop Container	DNV 2.7-1, BS EN 12079 & ISO/CSC	<p>Design, Manufacture & Certification</p> <ul style="list-style-type: none">- DNV 2.7-1 offshore containers- BS EN 12079:2006 offshore containers: Design, construction, testing, inspection, and marking- Classification Society: Lloyds Register- Certification: Third-party lifting certification provided for container and sling set <p>Other features</p> <ul style="list-style-type: none">- Insulation: PU sandwich panels, 50mm thick on sides and 100mm on roof- Electrics: Lighting, switch and power sockets 110v & 240V round plug/pin options - safe area- Work Area: Work bench complete with vice and under bench storage shelves- Storage: Removable bolted floor to roof storage cupboard with shelving and double doors- Lifting: Central runway beam complete with low headroom trolley / electric hoist - 10Te SWL with chain bag- Safety: Anti-slip studded rubber mat floor- Storage: Stackable to minimise deck area usage on location- Welfare: Ac units built into type & unis